



## STATIC PROPERTIES

NOMINAL THICKNESS	WEIGHT	MAX MOMENT IN THE SPAN	MAX MOMENT AT THE SUPPORT	I	W	SUPPORT REACTION
mm	kg/m <sup>2</sup>	kg.m	kg.m	cm <sup>4</sup>	cm <sup>3</sup>	kg
<b>0,60</b>	5,68	75,0	75,0	3,6	4,017	2105
<b>0,75</b>	7,09	89,3	89,3	4,3	4,789	3194

## SPAN TABLE

LOAD	THICKNESS	PURLIN SPACING				PURLIN SPACING			
		m				m			
kg/m <sup>2</sup>	mm	 DEFLECTION				 DEFLECTION			
		L/150	L/200	L/250	L/300	L/150	L/200	L/250	L/300
<b>60</b>	0,60	1,86	1,69	1,57	1,48	2,49	2,27	2,10	1,98
	0,75	1,98	1,79	1,66	1,57	2,65	2,74	2,23	2,10
<b>80</b>	0,60	1,69	1,54	1,43	1,34	2,27	2,06	1,91	1,80
	0,75	1,79	1,63	1,51	1,42	2,40	2,18	2,03	1,91
<b>100</b>	0,60	1,57	1,43	1,32	1,25	2,10	1,91	1,77	1,67
	0,75	1,66	1,51	1,40	1,32	2,23	2,03	1,88	1,77
<b>120</b>	0,60	1,48	1,34	1,25	1,17	1,98	1,80	1,67	1,57
	0,75	1,57	1,42	1,32	1,24	2,10	1,91	1,77	1,67
<b>150</b>	0,60	1,37	1,25	1,16	1,09	1,84	1,67	1,55	1,46
	0,75	1,46	1,32	1,23	1,15	1,95	1,77	1,64	1,55